

Instructions for attaching No. 3 adapter for Harris Engineering Bipods

Manufactured by Harris Engineering, Inc
Barlow, Kentucky 42021

The No. 3 adapter is designed to fit Remington semi-automatic rifles, models No. 4, 74 and 7400. The adapter consists of two parts, the base, and the fore-end screw.

Be sure the gun is unloaded and the action open before attaching Adapter or Bipod. Remove the existing fore-end screw, leave the cap in place. Mount the body of the adapter towards the rear of the gun. Tighten the adapter screw reasonable tight. If shooting loose is a problem, and this will generally not be the case, use a small amount of removable thread lock on the screw threads.

The Adapter will accept all Harris Engineering Bipods. However, the Models, BR, L, and LM are recommended. These low Bipods exert less strain on the fore-end. Attach the Bipod to fold the legs toward the muzzle.

Never reach across barrel muzzle or bring hands in line with barrel to fold or manipulate Bipod.

Limited Warranty: Guaranteed for one year from date of purchase against defects in materials and workmanship. Under no circumstances will guarantee extend beyond repair or replacement of adapter. Adapters may be returned directly to manufacturer by insured parcel post of UPS for repair or replacement. Harris Engineering, Inc. has no control over and assumes no responsibility for manner in which Bipods and Adapters are used.